



## Heskins Marine safety-grip data sheet

### Specification reference: H3460

Subject	Result	Test method
Back carrier	0.04mm PVC	Caliper method
Total applied thickness	0.99mm	Caliper method
Total thickness	1.2mm	Caliper method
Type of adhesive	Solvent acrylic	N/A
Mineral type	S2	N/A
Adhesion to steel (g/25.4mm <sup>2</sup> )	1500↑	PSTC-4
Tensile strength (Kg/25.4mm <sup>2</sup> )	5.0↑	PSTC-31
Elongation at break	5%↑	PSTC-31
Temperature range	-30°C to +70°C	See notes below
Maximum size of production roll	1060mm x 100m	N/A
Resistance to water (months)	10	PSTC-35
Resistance to chemicals (months)	8	PSTC-35
Resistance to motor oil	Excellent	PSTC-35
Life (months)	12 to 24	PSTC-9

*The independent test laboratory at Adhesive Technical Services Ltd performed the temperature test, England (test results available)*

### LRV Test Results

Material/Colour	Av. LRV	Range
H3460N (Black)	0	0
H3460B (Blue)	7	4
H3460S (Grey)	24.75	3





ANTI-SLIP SOLUTIONS  
[mail@heskins.com](mailto:mail@heskins.com)

[www.heskins.com](http://www.heskins.com)

05/06/2020

**Coefficient of friction data**

<b>Safety-Grip®</b>	<b>Dry surface test result</b>	<b>Wet surface test result</b>
<b>H3460</b>	96 TRL	42 TRL

*The above tests were conducted in accordance with Pendulum, the tests were conducted at a recognised independent friction testing laboratory, and copy certificates are available on request. Pendulum is a dynamic test, for static tests we also have results ASTM C 1028-96.*

All the above data is for reference only.

**©Heskins Ltd 1997-2020**

